

Specifications

miniLAB 1008



**MEASUREMENT
COMPUTING™**

Document Revision 1.5, May, 2006
© Copyright 2006, Measurement Computing Corporation

Specifications

Typical for 25 °C unless otherwise specified.

Specifications in *italic* text are guaranteed by design.

Analog Input

Parameter	Conditions	Specification
A/D converter type		Successive approximation type
Input voltage range for linear operation, single-ended mode	CHx to GND	± 10 V max
Input voltage range for linear operation, differential mode	CHx to GND	-10 V min, +20V max
<i>Absolute maximum input voltage</i>	<i>CHx to GND</i>	± 40 V max
Input current (Note 1)	$V_{in} = +10$ V	70 μ A typ
	$V_{in} = 0$ V	-12 μ A typ
	$V_{in} = -10$ V	-94 μ A typ
Number of channels		8 single-ended / 4 differential, software selectable
Input ranges, single-ended mode		± 10 V, G=2
Input ranges, differential mode		± 20 V, G=1 ± 10 V, G=2 ± 5 V, G=4 ± 4 V, G=5 ± 2.5 V, G=8 ± 2.0 V, G=10 ± 1.25 V, G=16 ± 1.0 V, G=20 Software selectable
Throughput	Software paced	50 S/s
	Continuous scan	1.2 kS/s
	Burst scan to 4K sample FIFO	8 kS/s
Channel gain queue	Up to 8 elements	Software configurable channel, range, and gain.
Resolution (Note 2)	Differential	12 bits, no missing codes
	Single-ended	11 bits
CAL accuracy	CAL = 2.5 V	± 0.05 % typ, ± 0.25 % max
Integral linearity error		± 1 LSB typ
Differential linearity error		± 0.5 LSB typ
Repeatability		± 1 LSB typ
CAL current	Source	5 mA max
	Sink	20 μ A min, 200 nA typ
Trigger source	Software selectable	External digital: DIO0-DIO3

Note 1: Input current is a function of applied voltage on the analog input channels. For a given input voltage, V_{in} , the input leakage is approximately equal to $(8.181 \cdot V_{in} - 12)$ μ A.

Note 2: The AD7870 converter only returns 11-bits (0-2047 codes) in single-ended mode.

Table 1. Accuracy, differential mode

Range	Accuracy (LSB)
$\pm 20\text{ V}$	5.1
$\pm 10\text{ V}$	6.1
$\pm 5\text{ V}$	8.1
$\pm 4\text{ V}$	9.1
$\pm 2.5\text{ V}$	12.1
$\pm 2\text{ V}$	14.1
$\pm 1.25\text{ V}$	20.1
$\pm 1\text{ V}$	24.1

Table 2. Accuracy, single-ended mode

Range	Accuracy (LSB)
$\pm 10\text{ V}$	4.0

Table 3. Accuracy components, differential mode - all values are (\pm)

Range	% of Reading	Gain Error at FS (mV)	Offset (mV)	Accuracy at FS (mV)
$\pm 20\text{ V}$	0.2	40	9.766	49.766
$\pm 10\text{ V}$	0.2	20	9.766	29.766
$\pm 5\text{ V}$	0.2	10	9.766	19.766
$\pm 4\text{ V}$	0.2	8	9.766	17.766
$\pm 2.5\text{ V}$	0.2	5	9.766	14.766
$\pm 2\text{ V}$	0.2	4	9.766	13.766
$\pm 1.25\text{ V}$	0.2	2.5	9.766	12.266
$\pm 1\text{ V}$	0.2	2	9.766	11.766

Table 4. Accuracy components, single-ended mode

Range	% of Reading	Gain Error at FS (mV)	Offset (mV)	Accuracy at FS (mV)
$\pm 10\text{ V}$	0.2	20	19.531	39.531

Analog output

Parameter	Conditions	Specification
D/A converter type		PWM
Resolution		10-bits, 1 in 1024
<i>Maximum output range</i>		<i>0 -5 Volts</i>
Number of channels		2 voltage output
Throughput	Software paced	100 S/s single channel mode 50 S/s dual channel mode
Power on and reset voltage		Initializes to 000h code
Maximum voltage (Note 3)	No load	Vs
	1 mA load	0.99 * Vs
	5 mA load	0.98 * Vs
Output drive	Each D/A OUT	30 mA
Slew rate		0.14 V/mS typ

Note 3: Vs is the USB bus +5V power. The maximum analog output voltage is equal to Vs at no-load. V is system dependent and may be less than 5 volts.

Digital input / output (screw terminal DIO3:0)

Parameter	Conditions	Specification
Digital type		Discrete, 5V/TTL compatible
Number of I/O		4
Configuration		4 bits, independently programmable for input or output.
Input high voltage		3.0 V min, 15.0 V absolute max
Input low voltage		0.8 V max
Output voltage (Note 4)	No load	Vs - 0.4 V min, Vs typ
	1 mA load	Vs - 1.5 V
<i>Input leakage current</i>		$\pm 1.0 \mu A$
Output short-circuit current (Note 4)	Output high	3.3 mA
Power-up / reset state		Input mode (high impedance)

Note 4: The DIO[3:0] lines available at the screw terminals are protected with 1.5 KOhm series resistors.

Digital input / output (DB37)

Digital type	82C55
Number of I/O	24 (Port A0 through Port C7)
Configuration	2 banks of 8 and 2 banks of 4, or 3 banks of 8
Pull up/pull-down configuration	All pins pulled up to Vs via 47K resistors (default). Positions available for pull down to ground. Hardware selectable via zero ohm resistor.
Input high voltage	2.0 V min, 5.5 V absolute max
Input low voltage	0.8 V max, -0.5 V absolute min
Output high voltage (IOH = -2.5 mA)	3.0 V min
Output low voltage (IOL = 2.5 mA)	0.4 V max

External trigger

Parameter	Conditions	Specification
Trigger source	External digital	DIO[3:0], only DIO may be selected as a trigger input
Trigger mode	Software selectable	Level sensitive: user configurable for TTL level high or low input.
Trigger latency	Burst	25 μs min, 50 μs max
Trigger pulse width	Burst	40 μs min
Input high voltage		3.0 V min, 15.0 V absolute max
Input low voltage		0.8 V max
<i>Input leakage current</i>		$\pm 1.0 \mu A$

Counters

Counter type	Event counter
Number of channels	1
<i>Input source</i>	<i>CTR screw terminal</i>
Input type	TTL, rising edge triggered
Resolution	32 bits
<i>Schmidt trigger hysteresis</i>	<i>20 mV to 100 mV</i>
<i>Input leakage current</i>	$\pm 1 \mu A$
Maximum input frequency	1 MHz
<i>High pulse width</i>	<i>500 ns min</i>
<i>Low pulse width</i>	<i>500 ns min</i>
Input low voltage	0V min, 1.0 V max
Input high voltage	4.0 V min, 15.0 V max

Non-volatile memory

Memory size	8192 bytes		
Memory configuration	Address Range	Access	Description
	0x0000 – 0x17FF	Read/Write	A/D Data (4k samples)
	0x1800 – 0x1EFF	Read/Write	User data area
	0x1F00 – 0x1FEF	Read/Write	Calibration Data
	0x1FF0 – 0x1FFF	Read/Write	System Data

Power

Parameter	Conditions	Specification
Supply Current (Note 5)		20 mA
+5V USB power available (Note 6)	Connected to Self-Powered Hub	4.5 V min, 5.25 V max
	Connected to Bus-Powered Hub	4.1 V min, 5.25 V max
Output Current (Note 7)	Connected to Self-Powered Hub	450 mA min, 500 mA max
	Connected to Bus-Powered Hub	50 mA min, 100 mA max

Note 5: This is the total current requirement for the miniLAB-1008 which includes up to 5mA for the status LED.

Note 6: Self-powered refers to USB hubs and hosts with a power supply. Bus-powered refers to USB hubs and hosts without their own power supply.

Note 7: This refers to the total amount of current that can be sourced from the USB +5V, analog outputs and digital outputs.

General

Parameter	Conditions	Specification
<i>USB controller clock error</i>	25 °C	$\pm 30 \text{ ppm max}$
	0 to 70 °C	$\pm 50 \text{ ppm max}$
	-40 to 85 °C	$\pm 100 \text{ ppm max}$
Device type		USB 1.1 low-speed
Device compatibility		USB 1.1, USB 2.0

Environmental

Operating temperature range	-40 to 85 °C
Storage temperature range	-40 to 85 °C
Humidity	0 to 90% non-condensing

Mechanical

Case dimensions	157 mm (L) x 102 mm (W) x40 mm (H) , including connectors
USB cable length	3 meters max
User connection length	3 meters max

Main connector and pin out

Connector type	Screw terminal
Wire gauge range	12 AWG to 22 AWG

4-channel differential mode

Pin	Signal Name	Pin	Signal Name
1	CH0 IN HI	16	DIO0
2	CH0 IN LO	17	DIO1
3	GND	18	GND
4	CH1 IN HI	19	DIO2
5	CH1 IN LO	20	DIO3
6	GND	21	GND
7	CH2 IN HI	22	D/A OUT 0
8	CH2 IN LO	23	D/A OUT 1
9	GND	24	GND
10	CH3 IN HI	25	CTR
11	CH3 IN LO	26	GND
12	GND	27	GND
13	PC +5V	28	PC +5V
14	PC +5V	29	PC +5V
15	CAL	30	TST

8-channel single-ended mode

Pin	Signal Name	Pin	Signal Name
1	CH0 IN	16	DIO0
2	CH1 IN	17	DIO1
3	GND	18	GND
4	CH2 IN	19	DIO2
5	CH3 IN	20	DIO3
6	GND	21	GND
7	CH4 IN	22	D/A OUT 0
8	CH5 IN	23	D/A OUT 1
9	GND	24	GND
10	CH6 IN	25	CTR
11	CH7 IN	26	GND
12	GND	27	GND
13	PC +5V	28	PC +5V
14	PC +5V	29	PC +5V
15	CAL	30	TST

DB37 connector and pin out

Connector type	37 D-Type, shielded
Compatible Cables	C37FF-x
	C37FFS-x
	C37FM-x
Compatible accessory products	CIO-MINI37 SSR-RACK24 SSR-RACK08 CIO-ERB24 CIO-ERB08

Pin	Signal Name	Pin	Signal Name
1	n/c	20	USB +5V Out
2	n/c	21	GND
3	Port B7	22	Port C7
4	Port B6	23	Port C6
5	Port B5	24	Port C5
6	Port B4	25	Port C4
7	Port B3	26	Port C3
8	Port B2	27	Port C2
9	Port B1	28	Port C1
10	Port B0	29	Port C0
11	GND	30	Port A7
12	n/c	31	Port A6
13	GND	32	Port A5
14	n/c	33	Port A4
15	GND	34	Port A3
16	n/c	35	Port A2
17	GND	36	Port A1
18	USB +5V Out	37	Port A0
19	GND		

Measurement Computing Corporation
16 Commerce Boulevard,
Middleboro, Massachusetts 02346
(508) 946-5100
Fax: (508) 946-9500
E-mail: info@mccdaq.com
www.mccdaq.com